

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

PCT

WORLD INTELLECTUAL PROPERTY
ORGANIZATION

INTERNATIONAL APPLICATION PUBLISHED UNIT

WO 9605475A1

WO 96/05475

(51) International Patent Classification 6 :

F25B 21/02, F25D 23/12

A1

(11) International Publication Number:

(43) International Publication Date: 22 February 1996 (22.02.96)

(21) International Application Number: PCT/US95/10263

(22) International Filing Date: 10 August 1995 (10.08.95)

(30) Priority Data: 08/288,459 10 August 1994 (10.08.94) US

(71) Applicant: AMERIGON, INC. [US/US]; 404 E. Huntington Drive, Monrovia, CA 91016 (US).

(72) Inventors: KARUNASIRI, Tissa, R.; 75-6 Gaynor Avenue, Van Nuys, CA 91406 (US). GALLUP, David, F.; 385 S. Catalina Avenue #103, Pasadena, CA 91106 (US). NOLES, David, R.; Apartment 201, 433 N. Louise Street, Glendale, CA 91206 (US). GREGORY, Christian, T.; 212 N. Cordova Street, Alhambra, CA 91801 (US).

(74) Agent: FISCHER, Felix, L.; Christie, Parker & Hale, Suite 500, 350 W. Colorado Boulevard, P.O. Box 7068, Pasadena, CA 91109-7068 (US).


(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TT, UA, UG, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, MW, SD, SZ, UG).

Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: VARIABLE TEMPERATURE SEAT CLIMATE CONTROL SYSTEM



(57) Abstract

A temperature climate control system (238) comprises a variable temperature seat (240), at least one heat pump (246), at least one heat pump temperature sensor (286), and a controller (290). Each heat pump comprises a number of Peltier thermoelectric modules (248) for temperature conditioning the air in a main heat exchanger (250) and a main exchanger fan (254) for passing the conditioned air from the main exchanger to the variable temperature seat. The Peltier modules and each main fan may be manually adjusted via a control switch (284) or a control signal. Additionally, the temperature climate control system may comprise a number of additional temperatures sensors (288) to monitor the temperature of the ambient air surrounding the occupant as well as the temperature of the conditioned air directed to the occupant. The controller is configured to automatically regulate the operation of the Peltier modules and/or each main fan according to a temperature climate control logic.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

1

VARIABLE TEMPERATURE SEAT CLIMATE CONTROL SYSTEM

5

Reference to Copending Patent Application

This application is a continuation-in-part of pending parent patent application Serial No. 08/156,052, filed on November 22, 1993.

10

Field of the Invention

The present invention relates generally to a variable temperature seat and, more specifically, to a method and apparatus for controlling the flow and temperature of a heating or cooling medium that heats or cools, directly or indirectly through the seat to an occupant positioned in such seat.

15

Background of the Invention

Cooling or heating occupants of buildings, homes, automobiles and the like is generally carried out by convection through modifying the temperature of air surrounding the occupants environment. The effectiveness of convection heating or cooling is largely dependent on the ability of the temperature conditioned air to contact and surround all portions of the occupant's body. Heating and cooling occupants through convection is generally thought to be efficient in such applications as homes, offices, and other like structures where the occupants are not stationary or fixed in one position but, rather are moving around allowing maximum contact with the temperature treated air.

25

In other applications such as automobiles, planes, buses and the like, the occupants are typically fixed in one position with a large portion of their body's surface against the surface of a seat, isolated from effects of the temperature conditioned air. In such applications the use of distributing temperature conditioned air into the cabin of the vehicle to heat or cool the occupant is less effective due to the somewhat limited surface area of contact with the occupant's body. In addition, oftentimes the surface of the seat is at a temperature close to the ambient temperature upon initial contact by the occupant, increasing the need to provide rapid temperature compensation to the occupant in an effective manner.

30

To address the problem of providing effective occupant heating or cooling in such applications, seats have been constructed to accommodate the internal flow of a heating or cooling medium and to distribute the same through the seating surface to the surface of the occupant in contact with the seat. A preferred heating and cooling medium is air. A seat constructed in this manner increases the efficiency of heating or cooling a passenger by

35

1 convection by distributing temperature conditioned air directly to the surface of the occupant
that is generally isolated from contact with temperature conditioned air that is distributed
throughout the cabin of the vehicle.

5 U.S. Patent No. 4,923,248 issued to Feher discloses a seat pad and backrest
comprising an internal plenum for distributing temperature conditioned air from a Peltier
thermoelectric module through the surface of the seat pad and to an adjacent surface of an
occupant. The temperature conditioned air is provided by using a fan to blow ambient air
over the fins of a Peltier module. The heating or cooling of the occupant is achieved by
changing the polarity of the electricity that powers the Peltier module.

10 U.S. Patent No. 5,002,336 issued to Feher discloses a joined seat and backrest
construction comprising an internal plenum for receiving and distributing temperature
conditioned air through the seat and to an adjacent surface of an occupant. Like U.S. Patent
No. 4,923,248, the temperature conditioned air is provided by a Peltier thermoelectric
module and distributed through the internal plenum by an electric fan.

15 U.S. Patent No. 5,117,638 issued to Feher discloses a selectively cooled or heated seat
construction and apparatus for providing temperature conditioned air. The seat construction
comprising, an internal plenum, a plastic mesh layer, a metal mesh layer, and perforated
outer layer. The apparatus for providing the temperature conditioned air is heat exchanger
comprising a Peltier thermoelectric module and a fan. Heating or cooling the occupant is
20 achieved by switching the polarity of the electricity powering the Peltier module.

The seat constructions known in the art, although addressing the need to provide a
more efficient method of heating or cooling the occupant, has not addressed the need to
provide temperature conditioned air to an occupant in a manner that both maximizes occupant
comfort and maximizes power efficiency. Further, seat constructions known in the art have
25 not addressed the possibility of directing temperature conditioned air to a second medium that
is in contact with the occupant to effect conductive heat transfer.

The ever increasing awareness of our environment and the need to conserve resources
has driven the need to replace hydrocarbon powered vehicles, such as the automobile, with
vehicles that are powered by an environmentally friendly power sources such as electricity.
30 The replacement of current hydrocarbon automobiles with electric powered vehicles will only
become a reality if the electric powered vehicle can be operated and maintained in a manner
equalling or bettering that of the hydrocarbon powered automobile it replaces. Accordingly,
the need for electric vehicles to perform in an electrically efficient manner, is important to
the success of the electric vehicle.

35 In order maximize the electrical efficiency of the electric powered vehicle it is
necessary that the electrically powered ancillary components of the electric vehicle function
at maximum electrical efficiency. The seats known in the art that provide temperature
conditioned air to an occupant do not operate in an electrically efficient manner. The

1 temperature of the air being conditioned by the Peltier thermoelectric devices in such seats
is adjusted by dissipating the excess power through a resistor, i.e., by using a potentiometer.
The practice of dissipating excess power instead of providing only that amount of power
5 power sensitive applications as the electric vehicle as well as other applications where
electrical efficiency is a concern.

The seats known in the art constructed to provided temperature conditioned air to an
occupant are adjustable in that the occupant may either choose to produce heated air or
cooled air. However, the seats known in the art are unable to automatically regulate the
10 temperature or flow rate of the cool or heated air being distributed to the occupant in the
event that the thermoelectric device malfunctions or in the event that the user falls asleep.
An electrical malfunctioning of the thermoelectric device could result in the abnormal heating
of the device, causing damage to the thermoelectric device itself. An electrical malfunction
could result in the distribution of hot air to the occupant and result in discomfort.
15 Additionally, an initial temperature setting of maximum heat or maximum cold that is left
untouched in the event the occupant falls asleep may cause damage to the thermoelectric
device itself or may cause discomfort or even injury to the occupant.

The seats known in the art, while able to vary the distribution of air to the seat bottom
or seat back via occupant adjustment, do not allow the occupant to vary the temperature of
20 the air passing to or through the seat back or seat bottom, independently. The option of
being able to selectively heat one portion of the seat and cool the other may be desirable
where the occupant requires such selective treatment due to a particular medical condition
or injury. For example, one a cold day it would be desirable to distribute heated air to the
seat back for occupant comfort and cooled air to the seat bottom to assist in healing a leg
25 injury that has recently occurred.

Additionally, seats known in the art do not provide for conductive cooling through a
non-perforated seating surface and rely entirely on convective heat transfer. Seats known in
the art do provide for conductive heating through use of resistance wire placed within the
seating surface. However, such seats cannot provide conductive cooling. Conductive heating
30 and cooling is an effective method of transferring heat or cold from a seating surface to
contacting portions of a seated occupant.

It is, therefore, desirable that a variable temperature seat comprise a control system
and method for regulating the temperature and flow rate of temperature conditioned air to
an occupant sitting in the seat. It is desirable that the control system operate the seat in an
35 electrically efficient manner, making it ideal for use in power sensitive applications such as
the electric powered vehicle. It is desirable that the control system operate the seat in a
manner eliminating the possibility of equipment damage, occupant discomfort or injury. It
is desirable that the control system permit the independent distribution of heated or cooled

1 air to the seat back or seat bottom. It is desirable that a variable temperature seat comprise
a control system capable of providing conductive as well as convective heat transfer to a
seated occupant. It is also desirable that the control system be easy to operate with minimal
occupant input.

5

Summary of the Invention

There is, therefore, provided in practice of this invention a temperature climate control
system for use with a variable temperature seat. The temperature climate control system
comprises a variable temperature seat suitable for distributing temperature conditioned air to
10 a seated occupant, at least one heat pump for temperature conditioning ambient air and
passing the air to the seat, a temperature sensor, and a controller configured to monitor the
temperature and regulate the operation of the heat pumps according to a temperature climate
control logic.

Each heat pump comprises a number of Peltier thermoelectric modules for selectively
15 heating or cooling ambient air in a main heat exchanger. The heated or cooled air is passed
to the seat by a main exchanger fan. Each heat pump also comprises a waste heat exchanger
for removing unwanted heat or cooling from the Peltier modules. The unwanted heat or
cooling is passed to the outside environment by a waste exchanger fan.

Each main fan may be manually adjusted to operate at a variety of predetermined
20 speeds via a fan switch. Each Peltier module can be manually adjusted to operate in various
heating or cooling modes via a temperature switch. The electrical power to each Peltier is
pulsed at a duty cycle corresponding to a particular heating or cooling mode of operation to
optimize electrical efficiency. Each heat pump may be operated independently via separate
fan and temperature switches, or may be operated simultaneously by a common fan and
25 temperature switch. Alternatively, each heat pump may be operated automatically by the
controller when the variable temperature seat is occupied by the activation of an occupant
presence switch.

After an initial fan speed and Peltier temperature setting has been selected, the
controller monitors the temperature information relayed from each heat pump. In addition,
30 the controller may also be configured to monitor the ambient temperature of the air
surrounding the variable temperature seat occupant as well as the temperature of the
conditioned air directed to the variable temperature seat occupant, via the use of additional
temperature sensors. The controller regulates the operation of each main exchanger fan, each
waste exchanger fan, and each Peltier module according to a temperature climate control
35 logic. The control logic is designed to maximize occupant comfort and minimize the
possibility of equipment damage, occupant discomfort or even occupant injury in the event
of a system malfunction.

The control logic is designed to interrupt or limit the power to the Peltier modules

1 and/or each main exchanger fan in the event that the heat pump temperature exceeds a
predetermined maximum temperature or a predetermined minimum temperature, indicating
a possible heat pump malfunction. Additionally, the control logic is designed to adjust power
to the Peltier modules in the event that the temperature of the conditioned air directed to the
5 variable temperature seat occupant exceeds a predetermined maximum or minimum
temperature.

The control logic is also designed to limit the power to the Peltier modules during the
cooling mode of operation when the temperature of the cooling air directed to the occupant
exceeds a predetermined minimum cooling temperature and the temperature has not been
10 adjusted for a predetermined period of time, thus minimizing possible occupant discomfort
associated with overcooling the occupant's back. In addition, the control logic is designed
to limit the power to the Peltier modules during the cooling mode of operation when the
temperature difference between the ambient air surrounding the variable temperature seat
occupant and the conditioned air directed to the occupant is greater than a predetermined
15 amount.

20

25

30

35

1 **Brief Description of the Drawings**

These and other features and advantages of the present invention will become appreciated as the same becomes better understood with reference to the specification, claims and drawings wherein:

5 FIG. 1 is a cross-sectional semi-schematic view of an embodiment of a variable temperature seat;

FIG. 2 is a schematic view of a first embodiment of a temperature climate control system according to the present invention;

10 FIG. 3 is a flow chart illustrating a temperature climate control logic for the embodiment of the invention shown in FIG. 2;

FIG. 4 is a schematic view of a second embodiment of a temperature climate control system according to the present invention;

FIG. 5 is a flow chart illustrating a temperature climate control logic for the embodiment of the invention shown in FIG. 4;

15 FIG. 6 is a schematic view of a third embodiment of a temperature climate control system according to the present invention;

FIG. 7 is a flow chart illustrating a temperature climate control logic for the embodiment of the invention shown in FIG. 6;

20 FIG. 8 is a schematic view of an alternative embodiment of a temperature climate control system according to the present invention;

FIG. 9 is a cross-sectional semi-schematic view of a second embodiment of a variable temperature seat without convective heat transfer channels;

FIG. 10 is a cross-sectional semi-schematic view of a third embodiment of a variable temperature seat including air channels for effecting conductive heat transfer;

25 FIG. 11 is a schematic view of a fourth embodiment of a temperature climate control system according to the present invention;

FIG. 12 is flow chart illustrating a cooling mode logic for a first controlling method used with the fourth embodiment of the invention shown in FIG. 11;

30 FIG. 13 is flow chart illustrating a heating mode logic for the first controlling method used with the fourth embodiment of the invention shown in FIG. 11;

FIG. 14 is flow chart illustrating a heating mode logic for a second controlling method used with the fourth embodiment of the invention shown in FIG. 11; and

FIG. 15 is flow chart illustrating a cooling mode logic for a third controlling method used with the fourth embodiment of the invention shown in FIG. 11.

35

1 Detailed Description

 A temperature climate control system (TCCS) provided in the practice of this invention may be used to control the temperature of a heat transfer medium, preferably air, being distributed through a variable temperature seat (VTS) and directed to a seated occupant. The
5 TCCS may be used in various VTS applications where it is required that an occupant stay seated for a period of time, such as automobiles, trains, planes, buses, dentists chairs, hair styling chairs and the like, or where an occupant simply desires an added degree of comfort while he/she is sitting at work or in the home, such as office chairs, home recliners and the like. The TCCS configured according to the practice of this invention to operate in a manner
10 providing an occupant seated in a VTS a maximum degree of comfort by allowing the occupant to manually adjust both the flow rate and the temperature of the air being passed through the seat surface and directed to the occupant.

 The TCCS is configured to automatically override the manual flow rate and temperature settings when it senses that the temperature of the air being directed to the
15 occupant is above a predetermined maximum temperature set point or is below a predetermined minimum temperature set point. Thus, maximizing both occupant comfort and occupant safety in the event that the occupant either falls asleep or in the event that the device generating the temperature conditioned air malfunctions. The TCCS also comprises
20 timers and is configured to automatically override the manual flow rate and temperature settings during normal operation to prevent back discomfort. Additionally, the device generating the temperature conditioned air is operated in a manner maximizing electrical efficiency, making it well suited for use in applications that are sensitive to electrical consumption, such as electric powered vehicles.

 FIG. 1 shows an embodiment of a VTS 10 comprising a seat back 12 and a seat
25 bottom 14 for accommodating the support of a human occupant in the sitting position. FIG. 1 shows a simplified cross-sectional view of a VTS for purposes of illustration and clarity. Accordingly, it is to be understood that the VTS may be constructed in embodiments other than that specifically represented. The VTS may be constructed having a outside surface
30 covering 16 made from a suitable material that allows the flow of air through its surface, such as perforated vinyl, cloth, leather or the like. A padding layer 17 such as reticulated foam may lie beneath the outside surface 16 to increase occupant comfort.

 The VTS may be constructed having a metal frame (not shown) that generally defines the seat configuration and having seat bottom and seat back cushions 18 made from foam and the like. A number of air channels 20 are positioned within each seat cushion and extend
35 from the padding layer 17 through the seat cushions and to either a seat bottom air inlet 22 or a seat back air inlet 24. Although a particular embodiment of a VTS has specifically described, it is to be understood that the TCCS according to the present invention is meant to operate with any type of VTS having the same general features.

1 FIG. 2 shows a first embodiment of the TCCS according to the present invention
comprising a VTS 10. The air that is passed through the seat and to the occupant is
temperature conditioned by a heat pump. This first embodiment comprises a seat back heat
pump 26 for temperature conditioning the air passed through the seat back 12 of the VTS,
5 and a seat bottom heat pump 28 for temperature conditioning the air passed through the seat
bottom 14 of the VTS. The seat back heat pump and seat bottom heat pump each comprise
at least one thermoelectric device 30 and 32, respectively, for temperature conditioning, i.e.,
selectively heating or cooling, the air. A preferred thermoelectric device is a Peltier
thermoelectric module. Each heat pump may comprise more than one Peltier thermoelectric
10 module. A preferred heat pump comprises approximately three Peltier thermoelectric
modules.

Each heat pump comprises a main heat exchanger 34 and 36, enclosing air temperature
conditioning fins (not shown) depending from one surface of the Peltier modules, and a waste
heat exchanger 39 and 40, enclosing thermal exchanger fins (not shown) extending from the
15 Peltier module surface opposite the main heat exchanger. Attached to one end of each main
heat exchanger is an outlet from a main exchanger fan 42 and 44 that serves to pass the
temperature conditioned air in each main heat exchanger to the seat back or seat bottom,
respectively. Each main exchanger fan may comprise an electrical fan having a suitable flow
rate, such as an axial blower and the like. The outlet end of each main heat exchanger is
20 connected to an air conduit 46 and 48 that is connected to the respective seat back air inlet
24 or seat bottom air inlet 22. Accordingly, the temperature conditioned air produced by the
Peltier thermoelectric modules in each main heat exchanger is passed through the respective
air conduit, through the respective air inlet, into and through the respective seat portion of
the VTS to the occupant by the main exchanger fan.

25 Attached to one end of each waste heat exchanger is an outlet from a waste exchanger
fan 50 and 52 that serves to pass unwanted waste heat or cooling produced in each waste heat
exchanger to the outside environment surrounding the VTS. Each waste exchanger fan may
comprise an electrical fan having a suitable flow rate, such as an axial blower and the like.
The waste air exiting each waste heat exchanger fan is usually at an undesirable temperature,
30 i.e., in the cooling mode it is hot air and in the heating mode it is cold air. Consequentially,
waste air exiting each waste exchanger may be specifically routed away from any occupant,
possibly through the sides of the seat or the like.

Attached to the main exchanger side of the Peltier thermoelectric modules in each heat
pump is a temperature sensor 54 and 56. Each temperature sensor may comprise an electric
thermocouple and the like.
35

The operation of the main exchanger fans 42 and 44 can be manually controlled by
a fan switch 58. In the first embodiment, it is preferred that the main exchanger fans are
operated simultaneously by a single fan switch. The fan switch may comprise an electrical

1 switch configured to provide an off position, and a variety of fan speed settings if desired. It is preferred that the fan switch be configured having an off position and three different fan speed settings, namely low, medium and high. The fan switch may be located within or near the VTS for easy occupant access.

5 The operation of the waste exchanger fans 50 and 52 can be manually controlled by a separate fan switch (not shown) if desired. However, it is preferred that the waste exchanger fans be activated automatically upon the operation of the main exchanger fans and operate at a single predetermined speed. Accordingly, upon the manual operation of the fan switch 58, both the main exchanger fans are activated to a selected speed and the waste
10 exchanger fans are automatically activated to operate at maximum speed. Configuring the TCCS to operate in this manner maximizes the thermal efficiency of the Peltier modules and reduces the possibility of system damage.

The operation of the Peltier thermoelectric modules can be controlled by a temperature switch 60. In the first embodiment it is preferred that the Peltier thermoelectric modules in
15 both heat pumps be operated simultaneously by a single temperature switch. The temperature switch may comprise an electrical switch configured to provide an off position, and a variety of temperature settings if desired. A preferred fan switch is configured having an off position, four heating positions, and four cooling positions. Like the fan switch 58, the temperature switch 60 may be located within or near the VTS for easy occupant access.

20 When the temperature switch is turned to one of the cooling positions a LED lamp 62 located near the temperature switch registers a green color, indicating that the Peltier modules are operating in the cooling mode. When the temperature switch is turned to one of the heating positions the LED lamp registers a red color, indicating that the Peltier modules are operating in the heating mode.

25 The different heating or cooling modes for the Peltier modules is accomplished by both switching the polarity and limiting the amount of the electrical power routed to the Peltier modules. To optimize the electrical efficiency of the Peltier modules, instead of using a potentiometer to discharge the unwanted portion of the electrical power through a resister, the four different modes of heating and cooling operation are achieved by pulsing electrical
30 power to the Peltier modules at predetermined duty cycles. Accordingly, the different levels of heating or cooling are accomplished by pulsing the electrical power to the Peltier modules at a predetermined duty cycle. In a preferred embodiment, the duty cycle is about 0.02 seconds (50 hz) and the four different levels are accomplished by applying either 25 percent, 50 percent, 75 percent, or 100 percent of the cycle time power. In this embodiment, a 25
35 percent duty cycle would be on for approximately 0.005 seconds and off for approximately 0.015 seconds for a total cycle length of 0.02 seconds, and then repeated. The 75 percent duty cycle is on for approximately 0.015 seconds and off for approximately 0.005 seconds.

The heating or cooling mode of the Peltier modules is achieved by switching the

- 1 polarity of the electrical power. The Peltier modules are configured to operate in the heating mode on approximately ten volts DC and in the cooling mode on approximately six volts DC. A DC converter may be positioned outside the controls to supply the heating and cooling voltage. The total duty cycle of the Peltier modules is adjustable from 0.02 to 0.2 seconds.
- 5 The power for the Peltier modules in each mode was chosen to optimize the efficiency and total thermal power supplied to an occupant of the VTS.

The electrical feeds to and/or outlets from the fan switch 58, temperature switch 60, main-exchanger fans 42 and 44, waste exchanger fans 50 and 52, Peltier thermoelectric modules 30 and 32 LED lamp 62, and temperature sensors 54 and 56 are routed to a

10 controller 64. Alternatively, the electrical feeds and signals may first be routed to a printed circuit board in the seat (not shown) that sends a signal to the controller. The controller comprises a power inlet 66 of sufficient electrical capacity to operate all of the aforementioned devices. The controller is configured to receive occupant inputs from the fan switch and the temperature switch and temperature information from the temperature sensors.

15 From this input the controller is configured to make adjustments to the operation of the heat pumps according to a predetermined logic designed to ensure occupant comfort and safety, and protect against system damage.

FIG. 3 is a flow chart illustrating a temperature climate control logic for the first embodiment of the TCCS shown in FIG. 2. The occupant wishing to use the VTS operates

20 the main exchanger fans by activating the fan switch 58 and selecting a desired fan speed (step 68). Upon the activation of the main exchanger fans the waste exchanger fans are also activated to operate at a maximum speed (step 70).

The occupant may activate the Peltier modules for temperature conditioning the air in the VTS by positioning the temperature switch 60 to a desired heating or cooling mode (steps

25 72 and 74). The Peltier modules can be manually deactivated by selecting the "off" position on the temperature control switch, in which case the power to the fans is maintained as indicated by the LED 62 registering a green color (step 76). Additionally, the Peltier modules are automatically deactivated by the controller when the fan switch is manually placed in the "off" position (step 78).

30 When the temperature switch is positioned to one of the four cooling modes the LED lamp 62 registers a green color (step 80). The temperature detected by the temperature sensors 54 and 56 in both heat pumps 26 and 28 is passed to the controller (step 82). If the temperature is below about 303°K (step 84) the power to the Peltier modules remains on (step 86), unless more than six minutes has elapsed since the time that the occupant has last

35 adjusted the temperature (step 88), in which case the power to the Peltier modules is reduced to 25 percent (step 90). It is desirable to reduce the power to the Peltier modules under such circumstances to prevent over cooling of the occupant's back, which has been shown to cause the occupant discomfort after use of the VTS. If the temperature is not below 303°K,

1 however, the power to the Peltier modules is maintained as indicated by the occupant controls (step 86).

5 When the temperature switch is positioned to one of the four heating modes the LED lamp 62 registers a red color (step 92). If the temperature is below about 339°K (step 94) the power to the Peltier modules remains on (step 96). If the temperature is in the range of from 339°K to 349°K (step 92) the power to the Peltier modules is reduced to 25 percent until the temperature is below 339°K (step 98). Reducing the power to the Peltier modules in this situation is desired to prevent the Peltier modules from overheating.

10 If the temperature of the main heat exchanger side of the Peltier modules is below either below 200°K or above 349°K (step 100), regardless of whether the Peltier modules are in the heating or cooling mode, the controller deactivates the Peltier modules (step 76) and maintains the operation of the main exchanger fans and waste exchanger fans. The occurrence of either of the above temperature conditions indicates a system malfunction. In this condition the LED lamp 62 registers a orange color, indicating a system malfunction.

15 The first embodiment comprises conditioned air temperature sensors 102 and 104 positioned in the air flow of the temperature conditioned air passing to the seat, back and seat bottom, respectively, as shown in FIG. 2. The conditioned air temperature sensors are electrically connected to the controller 64. The temperature climate control logic described above and illustrated in FIG. 3 is configured to deactivate the Peltier modules in the event that the temperature of the conditioned air is greater than about 325°K or below about 297°K. While the Peltier modules are deactivated the main exchanger fans continue to run.

20 FIG. 4 shows a second embodiment of the TCCS according to the practice of the present invention. The second embodiment is similar to the first embodiment in all respects, except for the addition of at least one ambient air temperature sensor 102 to monitor the temperature of the air outside of the VTS surrounding the occupant. The temperature sensor is electrically connected to relay ambient air temperature information to the controller 64. More than one ambient air temperature sensor may be used, each being positioned at different locations in the environment surrounding the occupant, to provide an ambient air temperature profile to the controller.

25 The second embodiment of the TCCS also differs from the first preferred embodiment in that the fan speed and air temperature for the seat back heat pump 26 and the seat bottom heat pump 28 can each be manually adjusted independently by using a separate seat back fan switch 104 and seat bottom fan switch 106, and a separate seat back temperature switch 108 and seat bottom temperature switch 110. The fan switches 104 and 106 and the temperature switches 108 and 110 in the second embodiment are the same as those previously described in the first embodiment. Alternatively, the TCCS may be configured having a single fan switch (not shown) to control the speed of fans 42 and 44 and two temperature switches (not shown) to control the power to each heap pump 26 and 28 independently. The TCCS may

1 also be configured having a single temperature switch (not shown) to control the power of
heat pumps 26 and 28 simultaneously and two fan switches to control the speed of each fan
42 and 44 independently.

5 LED lamps 112 and 114 are located near each temperature switch to indicate the mode
of operation selected for each heat pump, e.g., in the off position the LED lamps are off,
when both heat pumps are in the cooling mode the LED lamps register a green color, when
both heat pumps are in the heating mode the LED lamps register a red color, when there is
a temperature error or Peltier module malfunction in either heat pump the LED lamps fast
cycle red and green, registering an orange color.

10 Configuring the manual fan speed and temperature switches in this manner allows the
occupant the ability to operate the seat back 12 of the VTS at a different conditions than the
seat bottom 14. This may be desirable where a medical condition or injury requires that a
particular portion of the occupant's body be maintained at a temperature different from the
remaining portion of the occupant, e.g., where a leg injury requires cooling air in the seat
15 bottom of the VTS and the ambient temperature dictates that heated air pass through the seat
back for maximum occupant comfort.

Like the first embodiment, the electrical feeds to and/or outlets from the fan switches
104 and 106, temperature switches 108 and 110, main exchanger fans 42 and 44, waste
exchanger fans 50 and 52, Peltier thermoelectric modules 30 and 32, temperature sensors 54
20 and 56, LED lamps 112 and 114, and the ambient air temperature sensor 102 are routed to
the controller 64.

FIG. 5 is a flow chart illustrating a temperature climate control logic for the second
embodiment of the TCCS shown in FIG. 4. The control logic is similar to that previously
described above and shown in FIG. 3, except for the additional temperature inputs from the
25 ambient temperature sensor (step 116) and the conditioned air sensor, and except when the
Peltier modules are being operated in the cooling mode and the temperature of the
conditioned air from the seat back heat pump 26 is below about 310°K (step 119). When
the conditioned air temperature is below about 310°K, if it has been greater than six minutes
since the last temperature adjustment by the occupant (step 120), and the conditioned air
30 temperature of the conditioned is approximately 3°K or more below the temperature of the
ambient air surrounding the occupant (step 122), the controller reduces the power to the
Peltier modules in the seat back heat pump 26 to approximately 25 percent (step 124). If the
temperature is below about 310°K, but it has either been less than six minutes since the last
manual temperature adjustment or the conditioned air temperature is less than 3°K below the
35 ambient temperature, the power to the Peltier modules in the seat back heat pump remains
on at the occupant controlled setting (step 126).

Like the control logic described in FIG. 3, the reason for reducing the power to the
Peltier modules under such conditions is to regulate the amount of cooling air directed to an

1 occupant's back to prevent possible discomfort after using the VTS.

The second embodiment also comprises conditioned air temperature sensors 128 and 130 positioned in the air flow of the temperature conditioned air passing to the seat, back and bottom, respectively, as shown in FIG. 4. The conditioned air temperature sensors are
5 electrically connected to the controller 64. The temperature climate control logic described above and illustrated in FIG. 5 is configured to deactivate the Peltier modules in the event that the temperature of the conditioned air directed to the occupant is greater than about 325°K or below about 297°K. While the Peltier modules are deactivated the main exchanger
fans continue to run.

10 FIG. 6 shows a third embodiment of the TCCS according to the practice of this invention. The third embodiment is similar to the first embodiment in all respects except for two. One is the addition of at least one ambient air temperature sensor 132 to monitor the temperature of the air outside of the VTS surrounding the occupant. The temperature sensor is electrically connected to feed temperature information to the controller 64. More than one
15 ambient air temperature sensor may be used, each being positioned at different locations in the environment surrounding the occupant, to provide an ambient air temperature profile to the controller.

The second difference in the third embodiment of the TCCS is that only a single heat pump 134 is used to provide temperature conditioned air to both the seat back 12 and the seat
20 bottom 14. The single heat pump is similar to the seat back heat pump 26 and seat bottom heat pump 28 previously described in the first embodiment in that it comprises a main heat exchanger 136, a main exchanger fan 138, a waste heat exchanger 140, a waste exchanger fan 142 and a Peltier module temperature sensor 143. However, instead of three Peltier thermoelectric modules, the single heat pump 134 comprises four Peltier thermoelectric
25 modules 144. The temperature conditioned air from the main heat exchanger is passed to the seat back 12 and seat bottom 14 of the VTS by an air manifold 146 connected at one end to the outlet of the main heat exchanger 136 and at the other end to the seat back air inlet 24 and seat bottom air inlet 22. Alternatively, the third embodiment of the TCCS may comprise a double heat pump arrangement similar to that previously described in the first
30 embodiment.

The third embodiment of the TCCS also differs from the first embodiment in that the main exchanger fan speed and the heat pump air temperature are not manually adjustable by the occupant. Rather, the fan speed and the air temperature are controlled automatically by the controller 64. Additionally, an occupant presence switch 148 is located within the VTS
35 that is activated upon the presence of an occupant in the seat. The occupant presence switch may comprise a weight sensitive switch and the like located in the seat back or seat bottom. In a preferred embodiment, the occupant presence switch is located in the seat bottom and is electrically connected to the controller to relay the presence of an occupant. The use of

1 a occupant presence switch to control the activation of the VTS is desired for purposes of conserving electricity when the VTS is not occupied and when it is not practical or desirable to give individual control over the seats. e.g., in bus passenger seating applications.

5 FIG. 7 is a flow chart illustrating a temperature climate control logic for the third embodiment of the TCCS as shown in FIG. 6. The activation of the main exchanger fan 138 is controlled by an occupant sitting in the VTS (step 150), which activates the occupant presence switch, and the ambient conditions inside the vehicle as transmitted to the controller by the ambient temperature sensors (step 148). To ensure a rapid temperature response upon placement of an occupant in the VTS, the controller pulses electrical power to the Peltier
10 modules in the absence of an occupant at a steady state of voltage in the range of from 0.5 to 1 volt (step 152). The voltage that is actually applied during the duty cycle may be six or twelve volts. By maintaining a slow continuous pulse of power to the Peltier modules the transient time for achieving the desired temperature of conditioned air upon the presence of an occupant in the VTS is greatly minimized.

15 Once an occupant is seated in the VTS, the particular main fan speed and Peltier operating mode selected by the controller is dependent upon the ambient temperature surrounding the VTS occupant. When the ambient temperature is less than about 286°K (step 154) the controller selects a heating mode of operation and passes 100 percent power to the Peltier modules and operates the main exchanger fan at medium speed (step 156).
20 Upon the activation of the main exchanger fan the waste exchanger fan is also activated at high speed.

When the ambient temperature is between 286°K and 290°K (step 158) the controller selects a heating mode of operation and passes 75 percent power to the Peltier modules and operates the main exchanger fan at medium speed (step 160). When the temperature is
25 between 290°K and 293°K (step 162) the controller selects a heating mode of operation and passes 25 percent power to the Peltier modules and operates the main exchanger fan at medium speed (step 164).

When the ambient temperature is between 293°K and 297°K the (step 166) the controller pulses power to the Peltier modules at a steady state of approximately 0.5 volts and deactivates the main exchanger fan (step 168).
30

When the ambient temperature is between 297°K and 300°K (step 170) the controller selects a cooling mode of operation and passes 50 percent power to the Peltier modules and operates the main exchanger fan at medium speed (step 172). When the ambient temperature is between 300°K and 302°K (step 174) the controller selects a cooling mode of operation and passes 50 percent power to the Peltier modules and operates the main exchanger fan at
35 high speed (step 176). When the ambient temperature is above 302°K (step 178) the controller selects a cooling mode of operation and passes 100 percent power to the Peltier modules and operates the main exchanger fan at high speed (step 180).

1 In either the heating mode of operation (ambient temperatures up to 293°K) or the
cooling mode of operation (ambient temperatures above 297°K), a Peltier module
temperature (step 182) below 200°K or above 349°K (step 184) causes the controller to
5 deactivate the Peltier modules and maintain the operation of the main exchanger fan and
waste exchanger fan (Step 186). Either of the above conditions indicate a system
malfunction.

The third embodiment also includes a conditioned air temperature sensor 188
positioned in the air flow of the temperature conditioned air passing to the seat, as shown in
FIG. 6. The conditioned air temperature sensor is electrically connected to the controller 64.
10 The temperature climate control logic described above and illustrated in FIG. 7 is configured
to deactivate the Peltier modules 144 in the event that the temperature of the conditioned air
passing to the seat and to the occupant is greater than about 325°K or below about 297°K.
While the Peltier modules are deactivated the main exchanger fans continue to run.

The third embodiment of the TCCS as specifically described above and illustrated in
15 FIG. 6 is used for controlling multiple VTSs in multi-occupant applications such as buses,
trains, planes and the like. In such an application the main exchanger fan, waste exchanger
fan, Peltier modules, temperature sensor, and weight sensitive switch from each VTS are
electrically connected to a common controller. Multiple ambient air temperature sensors may
be placed at different locations within the vehicle to provide an accurate temperature profile
20 throughout the interior of the vehicle. The common controller is configured to accommodate
inputs from the multiple ambient air temperature sensors. The common controller may be
configured to control the main fan speed and mode of operation for the Peltier modules in
the same manner as that specifically described above and illustrated in FIG. 7, taking into
account the possibility of different ambient temperature zones within the vehicle surrounding
25 each VTS.

Although limited embodiments of the temperature climate control system have been
described and illustrated herein, many modifications and variations will be apparent to those
skilled in the art. For example, it is to be understood within the scope of this invention that
a temperature climate control system according to the present invention may comprise means
30 for automatically adjusting the flow of temperature conditioned air from a single heat pump
to the seat back or the seat bottom.

FIG. 8 illustrates an alternative embodiment of the third embodiment of the TCCS,
incorporating the use of valves 190 and 192 placed in the air manifold 146 leading to the seat
back and the seat bottom, respectively. The valves are activated electrically by a controller
35 64 according to a predetermined control logic. The control logic may be the same as that
specifically described above and illustrated in FIG. 7 for the third embodiment, with the
addition that controller limits the flow of cooling air to the seat back by closing valve 190
in the event that the occupant receives too much cooling air over a period of time. This

1 embodiment would help eliminate the occurrence of occupant discomfort after using the VTS.

FIG. 9 illustrates a second embodiment of a VTS 194 including a seat back 196 and seat bottom 198 for accommodating the support of a human occupant in a seated portion. The VTS 194 includes an outside surface covering 200 that is made from a suitable material
5 that allows the flow of air through its surface, such as cloth, perforated vinyl, perforated leather and the like. A padding layer 202, such as reticulated foam, is disposed beneath the outside surface covering 200 to increase occupant comfort. Unlike the first embodiment of the VTS 10 shown in FIG. 2, the VTS 194 does not include air channels that extend through
10 the seat bottom and seat back cushions 18. Rather, the VTS 194 includes seat bottom and seat back cushions 204 that extend from the padding layer 202 to an air inlet distributor 206 disposed along a backside surface of the seat back and seat bottom.

The seat bottom and seat back cushions 204 can be made from a porous material such as foam and the like that is capable of accommodating air flow therethrough, so that conditioned air introduced into each air distributor 206 is passed through the seat back and
15 seat bottom cushions, through the padding layer 202, through the surface covering 200 and onto the adjacent surface of a seated occupant. Accordingly, rather than passing conditioned air through the cushions via air channels disposed within the cushions, the conditioned air is passed through the cushion material itself. This avoids the need to manufacture seat back and seat bottom cushions having a number air channels therethrough and, therefore, reduces
20 the cost and time associated with manufacturing the VTS.

FIG. 10 illustrates a third embodiment of a VTS 208 including a seat back 210 and seat bottom 212 for accommodating the support of a human occupant in a seated portion. The VTS 208 includes an outside surface covering 214 that is made from a non-perforated material, such as vinyl, leather and the like. Unlike the first and second embodiments of
25 the VTS, the third embodiment of the VTS 208 relies on conductive heat transfer, rather than convective heat transfer, to providing heating and cooling to a seated occupant.

The VTS may include a padding layer 216 disposed beneath the outside surface covering 214 to provide added comfort to a seated occupant and improve air distribution beneath the seat cover. Seat back and seat bottom cushions 218 extend from the padding
30 layer 216 to a backside surface of each seat bottom and seat back. At least one air channel 220 is interposed between the padding layer 216 and the seat back and seat bottom cushions, and extends along a length of the seat bottom and seat back. The air channel 220 disposed within the seat bottom 212 comprises an air inlet channel 222 at one end of the seat bottom that extends through the seat cushion 218 to an inlet opening 224 at the backside of the seat
35 bottom, and an air outlet channel 226 at an opposite end of the seat bottom that extends through the seat cushion 218 to an outlet opening 228 at the backside of the seat bottom. The air channel 220 disposed within the seat back 210 comprises an air inlet channel 230 at one end of the seat back that extends through the seat cushion 218 to an inlet opening 232

1 at the backside of the seat back, and an air outlet channel 234 at an opposite end of the seat back that extends through the seat cushion 218 to an outlet opening 236 at the backside of the seat back.

5 The VTS 208 provides heating and cooling to a seated occupant via conductive heat transfer by recirculating temperature conditioned air against a backside surface of the padding layer 216. Alternatively, the VTS 208 may be constructed without the padding layer, with a padding layer of minimal thickness, or with a porous padding layer so that conditioned air recirculated through the air channels 220 is in direct contact with a backside surface of the surface covering 214 to better facilitate conductive heat transfer to the occupant seated on the
10 front side surface of the surface covering. As will be discussed in greater detail below, temperature conditioned air enters the seat bottom and seat back via respective air inlet openings 224 and 232, and is circulated across and/or through the padding layer 216 as it is passed through the respective air channels 220. The conditioned air exits the seat bottom and seat back via the respective outlet openings 228 and 236, is again conditioned within a heat
15 pump, and is directed again into each seat bottom and seat back.

Although particular embodiments of the VTS have been described and illustrated, it is understood that other embodiments of the VTS may be constructed that are within the scope of this invention. For example, an alternative embodiment of a VTS may include a hybrid configuration that provides heating and cooling to a seated occupant via both
20 convective and conductive heat transfer. In such embodiment, the VTS can be constructed having a number of air channels disposed therein to direct temperature conditioned air through a perforated portion of an outside surface covering to an adjacent surface of the seated occupant (such as that shown in FIGS. 1 and 10) to provide convective heating and cooling. In such embodiment, the VTS may also comprise a number of air channels disposed
25 along a backside surface of a non-perforated portion of the outside surface covering to accommodate recirculation of temperature conditioned air to provide conductive heat transfer to an adjacent surface of the seated occupant (such as that shown in FIG. 10). For example, the VTS can be configured with an outside surface covering having a non-perforated portion to facilitate conductive heat transfer positioned at the center of each seat bottom and seat
30 back, defining the primary seating surface, and a perforated portion to facilitate convective heat transfer posited at each side of the central portion, defining a peripheral portion of the seating surface.

Additionally, the VTS may be configured to facilitate conductive heat transfer to and from a seated occupant using a heat transfer medium other than air, such as water and the
35 like. Accordingly, in such an embodiment, the liquid heat transfer medium would be circulated through the seat and be in contact with a backside portion of a seating surface.

Additionally, an alternative embodiment of the VTS can be configured with valves and the like to effect convective heat transfer during initial operation of the VTS and switch to

1 conductive heat transfer after a predetermined state of operation has been achieved, by first
directing temperature conditioned air to the perforated portion of the seat, e.g., the side
edges of the seating surface, and then switching the routing of the temperature conditioned
air to the non-perforated portion, e.g., the central portion of the seating surface.

5 FIG. 11 illustrates a fourth embodiment of the TCCS 238 comprising a third
embodiment of the VTS 240 as described above and illustrated in FIG. 10. The TCCS is
configured to accommodate recirculation of temperature conditioned heat transfer medium,
preferably air, through the seat bottom 242 and seat back 244 to provide conductive heating
and cooling to a seated occupant. The TCCS comprises at least one heat pump 246 of the
10 type previously described for the first, second, and third embodiments of the TCCS and
illustrated in FIGS. 2, 4 and 6, including at least one Peltier thermoelectric module 248, a
main heat exchanger 250, a waste heat exchanger 252, and at least one fan. Accordingly,
the main heat exchanger and waste heat exchanger may be configured to share a common
fan. In a preferred embodiment, the heat pump comprises at least one main exchanger fan
15 254, and a waste exchanger fan 256.

The main exchanger fan 254 has an outlet connected to one end of the main exchanger
250 and serves to pass air that has been temperature conditioned by the Peltier modules
within the main exchanger to an inlet air manifold 258. The inlet air manifold is connected
to air inlet openings 260 and 262 in the seat bottom 242 and seat back 244, respectively, by
20 air inlet tubing 264. Temperature conditioned air is passed through the air inlet manifold 258
in parallel flow through the air inlet tubing, through the air inlet openings, and into the seat
bottom and seat back of the VTS.

Temperature conditioned air is routed through each seat bottom and seat back via at
least one air inlet channel 266 disposed through a seat cushion 268 at one end of the cushion,
25 at least one air channel 270 interposed between an outside surface cover 272 and the seat
cushion 268 and extending along a length of the seat bottom and seat back, and at least one
air outlet channel 274 disposed through the seat cushion at an opposite end of the cushion.
The temperature conditioned air passed through the air channels 270 is in contact with a
backside surface of the cover 272, effecting conductive heat transfer through its thickness,
30 and to a front side surface of the cover and to an adjacent surface of a seated occupant.

The temperature conditioned air exits the seat bottom and seat back via air outlet
openings 276 and 278, respectively, after it has effected conductive heat transfer to the
outside surface cover 272. Each air outlet opening is connected by air outlet tubing 280 to
an inlet end or intake 282 of the main exchanger fan 254. The temperature conditioned air
35 that exits the seat bottom and seat back is directed in parallel flow to the intake 282 of the
main fan 254 where it is passed by the fan into the main exchanger 250 and reconditioned
before again being introduced into the VTS. Accordingly, the TCCS 238 is configured to
accommodate the recirculation of temperature conditioned air through the VTS to

1 accommodate heating and cooling via conductive heat transfer.

The TCCS 238 comprises a control switch 284 for operation by a seat occupant to simultaneously activate operation of the Peltier thermoelectric modules 248, main exchanger fan 254, and waste exchanger fan 256 according to cooling and heating control logic described in detail below. The control switch 284 is an analog switch that is capable of being switched to an off position, or to provide a continuously variable temperature adjustment. For example, the control switch may be configured to provide a continuum of different cooling temperatures between approximately 65°F and 75°F, and a continuum of different heating temperatures between approximately 76°F and 85°F.

10 At least one temperature sensor 286, in the form of a thermocouple and the like, is attached to the main exchanger 250 of the heat pump 246 to provide an indication of the operating temperature of the Peltier modules 248. At least one temperature sensor 288, in the form of a thermocouple and the like, is also located within the inlet air manifold 258 to provide an indication of the temperature of the air exiting the main exchanger 250. The temperature sensors 288 may be mounted at other locations within the temperature conditioned air recirculation conduits as to provide further temperature information if desired.

Electrical leads to the Peltier modules 248, main exchanger fan 254, waste exchanger fan 256 extend from a controller 290. The controller comprises a power inlet 292 of sufficient electrical capacity to operate all of the aforementioned devices. The controller is configured to receive occupant input via the control switch 284, and to receive temperature information from the main exchanger temperature sensor 286 and conditioned air temperature sensor 288. From these inputs the controller is configured to make adjustments to the operation of the heat pump 246 and main exchange fan or fans 254 according to a predetermined cooling and heating control logic designed to ensure occupant comfort and safety, and protect against system damage.

20 The controller 290 is configured to route DC voltage in the range of from 0 to 12 volts to the Peltier modules 284. In the cooling mode, the controller can route up to about 6 volts DC to the Peltier modules depending on the particular set point cooling temperature and the temperature of the conditioned air. In the heating mode, the controller can route up to about 12 volts DC to the Peltier modules depending on the particular set point heating temperature and the temperature of the conditioned air. The controller 290 is configured to provide DC output to the Peltier modules at varied voltages, depending on the particular heating or cooling condition, rather than providing a fixed voltage that is pulsed over time.

30 The controller 290 is configured to monitor the current draw of the Peltier modules 284 and to limit the power consumption of the Peltier modules if the current draw exceeds a predetermined value as required by the power source. The controller monitors the current draw and regulates power consumption so that the Peltier modules are operated at a maximum allowed current at all conditions. In this manner, the controller ensures that the

1 maximum allowable current, as required by the power source, is not exceeded by the
operation of the Peltier modules. The need to regulate the power consumption of the Peltier
modules is especially important when the TCCS is used in applications powered by an
electrical source, such as an electric powered automobile. In such an application, regulating
5 the power consumption of accessory features has a direct impact on the range and driving
performance of the vehicle.

While the fourth embodiment of the TCCS 238 has been described and illustrated with
the third embodiment of the VTS 208, it is to be understood within the scope of this
invention that other embodiments of the VTS can also be used in conjunction with the TCCS
10 238. For example, the TCCS 238 can be used to provide temperature conditioned air to the
first and second embodiments of the VTS, 10 and 194, respectively, that are configured to
accommodate convective heat transfer to a seated occupant. To accommodate use of these
VTS embodiments with the TCCS 238 it may be necessary to modify the TCCS 238 by
removing the air outlet tubing 280 from the intake 282 of the main fan 254 so that the heat
15 pump does generate recirculating flow through the VTS. Rather the TCCS 238 configured
in this manner provide temperature conditioned air to the VTS that is then passed through
the VTS and to the seated occupant at the desired set point heating or cooling temperature.

FIG. 12 is a flow chart illustrating a cooling mode control logic 294 for a first
controlling method used to operate the TCCS 238 in a cooling mode of operation. An
20 occupant wishing to use the VTS 240 operates the control switch 284 to provide a desired
cooling temperature, i.e., sets the control to a cooling mode of operation (step 296).
Alternatively, the cooling mode of operation can be selected automatically by, for example,
thermostatic control based on a predetermined difference in temperature inside and outside
of the vehicle. This activates the controller 290, Peltier modules 248, the main exchanger
25 fan(s) 254 and waste exchanger fan(s) 256 (step 298). The waste fan(s) is operated at high
speed (step 300).

The main fan(s) is operated at a speed proportional to the cooling mode setting. For
example, if the cooling mode setting is low, i.e., a relatively high cooling temperature, the
main fan(s) is operated at a low speed. If the cooling mode setting is high, i.e., a relatively
30 low cooling temperature, the main fan(s) is operated at a high speed. And if the cooling
mode setting is medium, i.e., a moderate cooling temperature, the main fan(s) is operated
at a medium speed.

The Peltier modules are operated by receiving a level of power proportional to the
cooling mode setting (step 304). For example, if the cooling mode setting is low, i.e., a
35 relatively high cooling temperature, the Peltier modules receive a minimum level of power.
If the cooling mode setting is high, i.e., a relatively low cooling temperature, the Peltier
modules receive a maximum level of power. And if the cooling mode setting is medium,
i.e., a moderate cooling temperature, the Peltier modules receive a moderate level of power.

1 Accordingly, the cooling mode logic for the first controlling method regulates the operation of both the main fan(s) and the Peltier modules based on the particular cooling mode setting. The only input required by the seat occupant is the selection of a desired cooling temperature.

5 The cooling mode logic 294 monitors whether the Peltier modules have been operated for a predetermined length of time (step 306). In a preferred embodiment, the predetermined length of time is in the range of from 5 to 15 minutes. If the Peltier modules have not been operated for the predetermined length of time, power to the Peltier modules is maintained according to step 306. If the Peltier modules have been operated for the predetermined amount of time, the power to the Peltier modules is reduced to approximately 10 to 25 percent of the original power level (step 308). It is desired to decrease the amount of cooling provided to the VTS 240 after a predetermined amount of time to prevent overcooling a seated occupant's back, which has been shown to cause occupant discomfort.

15 If the occupant subsequently adjusts the control switch 284, or the control switch is automatically adjusted, to a new T_s (step 310) after the power to the Peltier modules has been reduced (step 306), the cooling mode logic 294 continues to regulate the speed of the main fan(s) in a manner proportional to the new cooling mode setting (step 302), and regulate the level of power directed to the Peltier modules in a manner proportional to the new cooling setting, but within the 10 to 25 percent reduced power of step 308 (step 312).

20 FIG. 13 is a flow chart illustrating a heating mode control logic 314 for a first controlling method used to operate the TCCS 238 in a heating mode of operation. An occupant wishing to use the VTS 240 operates the control switch 284 to provide a desired heating temperature, i.e., sets the control to a heating mode of operation (step 316). Alternatively, as mentioned above, the heating mode of operation can be selected automatically by, for example, thermostatic control based on a predetermined difference in temperature inside and outside of the vehicle. This activates the controller 290, Peltier modules 248, the main exchanger fan(s) 254 and waste exchanger fan(s) 256 (step 318).

25 The heating mode logic provides power to the Peltier modules at a level proportional to the heating mode setting (step 320). For example, if a low heating mode setting is selected, i.e., a relatively low heating temperature, a minimum level of power is directed to the Peltier modules. If a high heating mode setting is selected, i.e., a relatively high heating temperature, a maximum level of power is directed to the Peltier modules. The heating mode control logic also keeps the main fan(s) off and operates the waste fan(s) at high speed (step 320).

35 The heating mode control logic 294 monitors the temperature difference between a predetermined threshold temperature (T_t) and the temperature of the conditioned air (T_c) (step 322), as provided by the temperature sensor 288. If T_c is less than T_t (step 324), i.e., the temperature of the conditioned air is cooler than the threshold temperature, the power to

1 the Peltier modules is maintained at its original setting and the main fan(s) is off (step 320).
If T_c is greater than T_t (step 340), the main fan(s) is operated at low speed (328). In a
5 preferred embodiment, the predetermined threshold temperature is approximately 100°F. It
is to be understood that the threshold temperature is arbitrary and is largely a function of the
particular application of the TCCS and the particular embodiment of the VTS. It is desirable
to maintain power to the Peltier modules while keeping the main fan(s) off until the T_t is
reached to achieve a rapid temperature rise within the main heat exchanger 250 and, thereby
provide a rapid response time, i.e., reduce the time needed for the T_c to reach a
predetermined setpoint heating temperature.

10 Once the T_c is greater than the T_t , and the main fan(s) is operated, the heating mode
control logic 314 monitors the difference in temperature between a setpoint heating
temperature (T_s) and the T_c . If the T_c is less than the T_s (step 332), i.e., the temperature
of the conditioned air is below the heating mode setpoint temperature, the speed of the main
fan(s) proportional with the T_c (step 334). For example, as the T_c increases so does the
15 speed of the main fan(s). Increasing the main fan(s) speed with rising T_c until the T_s is
reached promotes a rapid response time as well as a greater heating effect discussed above.
If the T_c is equal to the T_s (step 336), the operation of the main fan(s) is maintained at the
existing speed setting (step 338). If the T_c is greater than the T_s (step 340), the speed of the
main fan(s) is increased proportionally with increased T_c (step 342). For example, as the
20 T_c increases so does the speed of the main fan(s). Increasing the speed of the main fan(s)
with increasing T_c helps to remove the excess heat that is generated by the heat pump,
thereby regulating the temperature of the conditioned air back to the T_s .

The heating mode logic 314 monitors the temperature of the heat pump (T_{hp}) 246, by
use of the temperature sensor 286, and determines whether the T_{hp} exceeds a predetermined
25 maximum temperature (T_m) (step 344). If the T_{hp} is greater than the T_m , the power to the
Peltier modules is shut off and the main fan(s) speed is maintained until the T_{hp} falls below
the T_m (346). In a preferred embodiment the predetermined maximum temperature is
approximately 100°F. A heat pump temperature above the predetermined maximum
temperature indicates that a malfunction in the heat pump has occurred. Shutting off power
30 to the Peltier modules ensures that a seated occupant will not be harmed or suffer discomfort
as a result of such malfunction.

A second controlling method for use with the TCCS 238 described and illustrated
above includes a cooling mode control logic that is identical to the cooling mode control logic
294 described above and illustrated in FIG. 12 for the first controlling method. FIG. 14 is
35 a flow chart illustrating a heating mode control logic 348 of the second controlling method
used to operate the TCCS 238 in a heating mode of operation. An occupant wishing to use
the VTS 240 operates the control switch 284 to provide a desired heating temperature, i.e.,
sets the control to a heating mode of operation (step 350). Alternatively, as mentioned above,

1 the heating mode of operation can be selected automatically by, for example, thermostatic control based on a predetermined difference in temperature inside and outside of the vehicle. This activates the controller 290, Peltier modules 248, the main exchanger fan(s) 254 and waste exchanger fan(s) 256 (step 352).

5 The heating mode control logic 348 directs power at a maximum level to the Peltier modules, keeps the main fan(s) off, and operates the waste fan(s) at a high speed (step 354). The temperature difference between a predetermined temperature (T_i) and the temperature of the conditioned air (T_c), via the temperature sensor 288 is monitored (step 356). If the T_c is less than the T_i (step 358), i.e., the temperature of the conditioned air is below the predetermined temperature, the level of power directed to the Peltier modules is maintained and the main fan(s) is off (step 354). Like the heating mode control logic 314 for the first controlling method, maintaining maximum power to the Peltier modules while keeping the main fan(s), until a predetermined temperature is achieved, provides a rapid response from the time that the TCCS is activated to the time that a desired heating setpoint temperature is reached.

15 If the T_c is greater than the T_i (step 360), i.e., the temperature of the conditioned air is higher than the predetermined temperature, the main fan(s) is operated at low speed (step 362), maximum power to the Peltier modules is maintained (step 354), and the temperature difference between T_i and T_s is continuously monitored (step 356).

20 The heating mode control logic 348 monitors the difference in temperature between a setpoint heating temperature (T_s) and the T_c (step 364). If the T_c is less than the T_s (step 366), i.e., the temperature of the conditioned air is below the setpoint heating temperature, the main fan(s) speed is increased in proportion with increased T_c (368). For example, as the temperature of the conditioned air increases, the speed of the main fan(s) is increased. And conversely, as the temperature of the conditioned air decreases, the temperature of the main fan(s) is decreased. As the T_c approaches T_s , the temperature difference between the two are constantly monitored (step 364).

25 If the T_c is equal to the T_s (step 370), the power to the Peltier modules is switched on and off, in the manner described above for the fourth embodiment of the TCCS 238, and the speed of the main fan(s) is unchanged (step 372). Accordingly, unlike the heating mode control logic 314 of the first controlling method described above, the power is routed the Peltier modules at a maximum level and is switched on and off for heat output adjustment, rather than receiving a level of power proportional to the heating mode setting.

30 The heating mode logic 348 monitors the temperature of the heat pump (T_{hp}) 246, by use of the temperature sensor 286, and determines whether the T_{hp} exceeds a predetermined maximum temperature (T_m) (step 374). If the T_{hp} is greater than the T_m , the power to the Peltier modules is shut off and the main fan(s) speed is maintained until the T_{hp} falls below the T_m (step 376). A heat pump temperature above the predetermined maximum temperature

1 indicates that a malfunction in the heat pump has occurred. Shutting off power to the Peltier modules ensures that a seated occupant will not be harmed or suffer discomfort as a result of such malfunction.

5 A third controlling method for use with the TCCS 238 described and illustrated above includes a heating mode control logic that is identical to the heating mode control logic 348 described above and illustrated in FIG. 14 for the second controlling method. FIG. 15 is a flow chart illustrating a cooling mode control logic 378 of the third controlling method used to operate the TCCS 238 in a cooling mode of operation. An occupant wishing to use the VTS 240 operates the control switch 284 to provide a desired cooling temperature, i.e., sets
10 the control to a cooling mode of operation (step 380). Alternatively, as mentioned above, the cooling mode of operation can be selected automatically by, for example, thermostatic control based on a predetermined difference in temperature inside and outside of the vehicle. This activates the controller 290, Peltier modules 248, the main exchanger fan(s) 254 and waste exchanger fan(s) 256 (step 382).

15 The main fan(s) is operated at a speed proportional to the cooling mode setting (step 384). For example, if the cooling mode setting is low, i.e., a relatively high cooling temperature, the main fan(s) is operated at a low speed. If the cooling mode setting is high, i.e., a relatively low cooling temperature, the main fan(s) is operated at a high speed. And if the cooling mode setting is medium, i.e., a moderate cooling temperature, the main fan(s)
20 is operated at a medium speed. The waste fan(s) is operated at high speed (step 384).

The cooling mode control logic 378 monitors the difference in temperature between the temperature of the conditioned air (T_c), via the temperature sensor 288, and a setpoint cooling temperature (T_s) (step 386). If the T_c is greater than the T_s (step 388), i.e., the temperature of the conditioned air is above the setpoint cooling temperature, a maximum
25 level of power is directed to the Peltier modules (step 390), and the temperature difference between T_c and T_s is continuously monitored. If the T_c is less than the T_s (step 392), a minimum level of power is directed to the Peltier modules (step 394), and the temperature difference between T_c and T_s is continuously monitored. If the T_c is less than a predetermined minimum temperature (T_m) (step 396), power to the Peltier modules is shut
30 off and the main fan(s) speed remains unchanged (step 398). A T_c below T_m indicates a malfunction in the heat pump and shutting off the Peltier modules ensures that a seated occupant will experience discomfort or harm from such malfunction.

If the T_c is equal to the T_s (step 400), the power to the Peltier modules is switched on and off to maintain the T_s , the speed of the main fan(s) remains unchanged (step 402),
35 and the temperature difference between T_c and T_s is continuously monitored (step 386). Accordingly, once the T_s is achieved, the power to the Peltier modules is adjusted, rather than the fan speed, to maintain the T_s . The cooling mode control logic 378 monitors the length of time that the Peltier modules have been operated and reduces the level of power

1 directed to the Peltier modules to 10 to 25 percent of the original power level after a
predetermined amount of time as passed (step 404). The speed of the main fans remain
unchanged (step 404). In a preferred embodiment, the length of time is in the range of from
5 to 15 minutes. It is desired to decrease the amount of cooling provided to the VTS 240
5 after a predetermined amount of time to prevent overcooling a seated occupant's back, which
has been shown to cause occupant discomfort.

Although the cooling and heating mode control logic for the first, second, and third
controlling methods have been described above as being used with the fourth embodiment
of the TCCS 238. It is to be understood that the first, second, and third controlling methods
10 can be used with the other TCCS embodiments of this invention. For example, the first,
second, and third controlling methods can be used to provide temperature conditioned air to
a VTS configured to accommodate convective heat transfer to a seated occupant, as shown
in FIG.

It is also to be understood that the embodiments of the TCCS described above and
15 illustrated in FIGS. 1, 4, 6, 8 and 11 have been presented in a form to promote clarity and
understanding of the invention. Accordingly, the TCCS system may be configured
differently than illustrated. For example, the heat pumps used to provide temperature
conditioned air to the VTS can be mounted within the seat bottom and/or seat back of the
VTS itself, rather than being mounted external to the VTS. Additionally, the controller and
20 control switches can also be mounted within the VTS itself.

The embodiments of the TCCS described above and illustrated can also be configured
to provide temperature conditioned air to more than one VTS. For example, the TCCS
illustrated in FIGS. 1, 4, 6, 8 and 11 can provide temperature conditioned air to a number
of VTS seats using parallel air flow from one or more heat pumps operated by a respective
25 TCCS heating and cooling control logic. Such an embodiment would be particularly useful
in applications related to public transportation, such as planes, buses, trains and the like,
where a number of occupants remain seated for extends period while traveling.

In addition to the embodiments of the TCCS specifically described above and
illustrated, it is to be understood that such the TCCS may incorporate input from an energy
30 management system, such as that used in electric powered vehicles. In specific
embodiments, the TCCS is configured to accept an inhibit signal from such an energy
management system. The inhibit signal is typically activated by a vehicle's energy
management system under particular conditions of operation when an additional amount of
energy is required or when the battery is being discharged to rapidly, such as during hard
35 acceleration, when climbing a hill, or when the battery is weak or is approaching its
minimum discharge voltage. The temperature climate control logic according to the present
invention can be configured to deactivate the Peltier modules, the main exchanger fans, and
the waste exchanger fans upon activation of the inhibit signal.

1 Accordingly, it is to be understood that, within the scope of the appended claims, the
temperature climate control system according to principles of this invention may be embodied
other than as specifically described herein.

5

10

15

20

25

30

35

1 **WHAT IS CLAIMED IS:**

1. A system for controlling the temperature climate in a variable temperature occupant seat, the system comprising:

5 an occupant seat having internal air channels disposed therein for circulating temperature conditioned air therethrough, wherein at least one air channel is positioned adjacent an outside surface covering of the seat for effecting conductive heat transfer to and from a seated occupant;

 a heat pump having an air outlet connected to an air inlet of the seat;

10 a control switch for simultaneously activating the system and selecting a desired heating or cooling mode of operation; and

 a controller for automatically regulating the operation of the heat pump to provide temperature conditioned air according to the selected heating or cooling mode of operation.

15 2. The system as recited in claim 1 wherein the heat pump comprises:

 a number of thermoelectric modules for temperature conditioning the air;

 at least one main exchanger fan for passing the temperature conditioned air through the air outlet to the seat; and

20 at least one waste exchanger fan for removing unwanted thermal energy from the thermoelectric modules.

3. The system as recited in claim 2 wherein the heat pump comprises a common main exchanger and waste exchanger fan.

25 4. The system as recited in claim 2 comprising means for recirculating temperature conditioned air from the heat pump, through the seat, and back to the heat pump.

30 5. The system as recited in claim 4 wherein the means for recirculating temperature conditioned air comprises an air outlet connected at one end to an air channel within the seat, and connected at an opposite end to an air inlet of the heat pump, wherein temperature conditioned is recirculated by the heat pump through the seat via the air inlet, the air channels, and air outlet.

35 6. The system as recited in claim 1 wherein the seat comprises a seat back portion and a seat bottom portion, wherein each back and bottom portion comprises an air inlet and an air outlet connected to an air channel disposed within each seat portion.

1 7. The system as recited in claim 6 wherein an air outlet end of the heat pump is
connected in parallel with the air inlet of each seat bottom and seat back, and wherein an air
inlet end of the heat pump is connected in parallel with the air outlet of each seat bottom and
seat back to recirculate temperature conditioned air through the seat.

5 8. A method for controlling the temperature climate in a variable temperature
occupant seat, the method comprising the steps of:
 selecting a desired cooling level;
 activating a number of thermoelectric modules to temperature condition a heat transfer
10 medium to a desired cooling temperature;
 activating at least one transporting means mounted adjacent the thermoelectric modules
for passing temperature conditioned heat transfer medium from the modules to a variable
temperature seat;
 monitoring the temperature of the temperature conditioned heat transfer medium; and
15 automatically regulating the operation of the thermoelectric modules and the
transporting means to achieve the desired cooling temperature.

 9. The method as recited in claim 8 wherein the heat transfer medium is air and
the transporting means is a fan.

20 10. The method as recited in claim 9 comprising the step of automatically operating
the fan at a speed proportional to the desired cooling level.

 11. The method as recited in claim 10 comprising the step of automatically
25 operating the thermoelectric modules at a power level proportional to the desired cooling
level.


 12. The method as recited in claim 10 comprising the step of monitoring a
30 difference in temperature between the temperature conditioned heat transfer medium and the
desired cooling temperature.

 13. The method as recited in claim 10 comprising the step of automatically
regulating the amount of electrical power directed to the thermoelectric modules based on the
temperature difference.

35 14. The method as recited in claim 13 comprising directing a maximum level of
electrical power to the thermoelectric modules when the temperature of the temperature
conditioned heat transfer medium is greater than the desired cooling temperature.

- 1 15. The method as recited in claim 13 comprising directing a minimum level of electrical power to the thermoelectric modules when the temperature of the temperature conditioned heat transfer medium is less than the desired cooling temperature.
- 5 16. The method as recited in claim 13 comprising switching the electrical power to the thermoelectric modules on and off when the temperature of the temperature conditioned heat transfer medium is equal to the desired cooling temperature to maintain the desired cooling temperature.
-
- 10 17. The method as recited in claim 10 comprising reducing the amount of electrical power directed to the thermoelectric modules if the desired cooling temperature has been achieved for a predetermined amount of time.
- 15 18. The method as recited in claim 17 comprising reducing the amount of electrical power directed to the thermoelectric modules in the range of from 10 to 25 percent.
19. A method for controlling the temperature climate in a variable temperature occupant seat, the method comprising the steps of:
 selecting a desired heating mode level;
20 activating a number of thermoelectric modules to temperature condition a heat transfer medium to a desired heating temperature;
 activating at least one transporting means for passing the temperature conditioned heat transfer medium into a variable temperature seat;
 monitoring the temperature of the temperature conditioned heat transfer medium; and
25 automatically regulating the operation of the thermoelectric modules and transporting means to achieve the desired heating temperature.
20. The method as recited in claim 19 wherein the heat transfer medium is air and the transporting means is a fan.
- 30 21. The method as recited in claim 20 comprising directing electrical power at a maximum level to the thermoelectric modules and not operating the fan if the temperature of the conditioned air is below the predetermined threshold temperature.
- 35 22. The method as recited in claim 21 comprising operating the fan at a low speed if the if the temperature of the conditioned air is at or above the predetermined threshold temperature.

- 1 23. The method as recited in claim 21 comprising monitoring a difference in temperature between the desired heating temperature and the temperature of the conditioned air.
- 5 24. The method as recited in claim 23 comprising increasing the speed of the fan proportionally with increasing temperature of the temperature conditioned air when the temperature of the temperature conditioned air is greater than the desired heating temperature.
- 10 25. The method as recited in claim 23 comprising switching the electrical power directed to the thermoelectric modules on and off when the temperature of the temperature conditioned air is equal to the desired heating temperature for maintaining the desired heating temperature.
- 15 26. The method as recited in claim 20 comprising directing electrical power to the thermoelectric modules at a level proportional to the desired heating level, and not operating the fan.
- 20 27. The method as recited in claim 26 comprising monitoring a temperature difference between a predetermined threshold temperature and the temperature of the temperature conditioned air.
- 25 28. The method as recited in claim 26 comprising operating the fan at low speed if the temperature of the conditioned air is greater than the predetermined threshold temperature.
- 30 29. The method as recited in claim 26 comprising monitoring a difference in temperature between the desired heating temperature and the temperature of the conditioned air.
- 35 30. The method as recited in claim 29 comprising operating the speed of the fan in proportion to the the temperature of the temperature conditioned air when the temperature of the temperature conditioned air is less than or greater than the desired heating temperature.
31. The method as recited in either one of claims 23 or 26 comprising monitoring the temperature of the heat pump and shutting of electrical power to the thermoelectric modules if the temperature of the heat pump is greater than a predetermined maximum temperature.







Fig. 2

3/15

Fig. 3








Fig. 4

5/15







SUBSTITUTE SHEET (RULE 26)

7/15

Fig. 7



9/15



SUBSTITUTE SHEET (RULE 26)





FIG. 11

SUBSTITUTE SHEET (RULE 26)


12/15

FIG. 12




13/15

FIG. 13




14/15



15/15

FIG. 15

SUBSTITUTE SHEET (RULE 26)



INTERNATIONAL SEARCH REPORT

International application No.
PCT/US95/10263**A. CLASSIFICATION OF SUBJECT MATTER**

IPC(6) : F25B 21/02; F25D 23/12

US CL : 62/3.5, 3.61, 261

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 62/3.5, 3.61, 261, 3.3; 236/49.3

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched
NoneElectronic data base consulted during the international search (name of data base and, where practicable, search terms used)
None**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US, A, 4,923,248 (FEHER) 08 May 1990, column 2, lines 51-63.	1-31
Y	US, A, 4,777,802 (FEHER) 18 October 1988, column 7, line 63 to column 8, line 58.	1-31
Y	US, A, 3,653,589 (McGRATH) 04 April 1972, column 1, line 69 to column 2, line 6.	10-18, 22, 24, 28, 30
A	US, A, 3,552,133 (LUKOMSKY) 05 January 1971, see the entire document.	1-31
A	US, A, 4,905,475 (TUOMI) 06 March 1990, see the entire document.	1-31
A	US, A, 3,136,577 (RICHARD) 09 June 1964, see the entire document.	1-31

☐ Further documents are listed in the continuation of Box C.
 ☐ See patent family annex.

* Special categories of cited documents:	* T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
* A* document defining the general state of the art which is not considered to be of particular relevance	* X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
* E* earlier document published on or after the international filing date	* Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
* L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	* &* document member of the same patent family
* O* document referring to an oral disclosure, use, exhibition or other means	
* P* document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

25 OCTOBER 1995

Date of mailing of the international search report

11 JAN 1996

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

WILLIAM E. TAPOLCAI

Telephone No. (703) 308-2640